Amendments to the Specification

Please replace the paragraph beginning on page 2, line 21 and ending on page 3, line 16 with the following rewritten paragraph:

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

1

2

3

On the transmitter side of the communication channel, the analog signal has a baseband bandwidth of +/-f and is converted to n bit data words by the analog to digital converter at a sampling rate exceeding the Nyquist rate of 2f samples per second. These n bit data words are parallel data bit signals that are converted into a serial bit stream at a rate of 2fn bps. To determine the ordering of the least to most significance bits of the data words in the serial bit stream, unique and easily identifiable synchronization frame words are periodically inserted into the serial data stream. These synchronization frames words are overhead data and are typically one to ten percent of the informational data words. This overhead data increases the required rate of bits transmitted per second to (2fn(1+s/100)bps where s is the percentage of the serial bit stream associated with synchronization frame words. To accomplish the communications at the original data bit, the serial stream including the frame words and redundant error correction bits must be reclocked to a higher data rate having a shorter bit duration time. In order to maintain data rate of the data words when the serial bit stream has additional synchronization frame words, the serial bit stream will be clocked at a higher rate by bit synchronization. The received data stream must also therefore be coherently reclocked to recover the original data. Non-integer multiples of the transmitted data require frequency synthesizers and other digital word buffers.

Please replace the paragraph beginning on page 11, line 14 and ending on page 12, line 9 with the following rewritten paragraph:

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

1

2

The laser crosslink is well suited for use in small satellites such as nanosatellites having very limited power resources. crosslink has a reduced number of components reducing power requirements. One application of small satellites is a signal receiver that transmits digitized copies of the received signals to other satellites for processing. This has uses in either signal intelligence or for digital nonregenerative transponders. The laser crosslink offers lower power consumption and fewer parts by integrating a modulator and A/D converter with the transmitter and receiver. The laser crosslink reduces filter requirements for small satellite using direct modulation of a laser while reducing manufacturing tolerances for smaller satellite. No specialized modulator is required by the laser. No error correction is required because redundancy is added by the over sampling of the sigma delta converter. No bit or frame synchronization is needed between the two satellites because the output of the digital filter may be sampled at any time to reconstruct signal samples, that is, the communication is asynchronous. No framing is needed in the data stream because the data stream is self-synchronizing. Also, there is no need to order bits from most to least significant bits as in traditional digital data links because only the duration of the bit time is required for proper data detection. These and other advantages will become more apparent from the following detailed description of the preferred embodiment.

28 ///

Please replace the paragraph beginning on page 18, line 1 and ending on page 18, line 10 with the following rewritten paragraph:

The laser communication crosslink system is preferably used for communicating analog signals in digital form. The laser communication crosslink system need not use parallel to serial conversion, frame synchronization, data reclocking bit synchronization, nor forward error correction. An analog signal may be communicated over the communication medium in digital form for recovering a digital value of the analog signal. Those skilled in the art can make enhancements, improvements, and modifications to the invention, and these enhancements, improvements, and modifications may nonetheless fall within the spirit and scope of the following claims.

28 | //